

IBOCO's NEW Cable Glands

IBOCO's new glands are made of Polyamide 6 neoprene seal and are resistant to salt water, ether, gasoline, weak alcohols and alkalis. They can be terminated, and easily installed, onto electrical cables and cords that are installed into enclosures, pumps, motors and generators.



TECHNICAL DETAILS:

Material:-----Polyamide 6
 Protection Class:-----IP 68 - 5 bar
 Operating Temp:-----Permanent -30°C to +80°C
 Intermittent -30°C to +150°C
 Seal:-----Neoprene


NPT* - Thread Cable Glands – Comes complete with lock nut and gaskets.

GREY – RAL 7035

CATALOG NUMBER	Size (NPT)	Cable Clamping Diameter		TD inches	TL Inches	ØD inches
		Inches	Millimeters			
CG-110G	3/8"	.197 - .394	5 - 10	.653	.590	.98
CG-120G	1/2"	.197 - .354	5 - 9	.809	.590	1.09
CG-121G	1/2"	.276 - .472	7 - 12	.809	.590	1.09
CG-122G	1/2"	.394 - .551	10 - 14	.809	.590	1.21
CG-131G	3/4"	.551 - .709	13 - 18	1.020	.590	1.49
CG-140G	1"	.709 - .984	18 - 25	1.275	.709	1.89

BLACK - RAL 9005

CATALOG NUMBER	Size (NPT)	Cable Clamping Diameter		TD inches	TL Inches	ØD inches
		Inches	Millimeters			
CG-110K	3/8"	.197 - .394	5 - 10	.653	.590	.98
CG-120K	1/2"	.197 - .354	5 - 9	.809	.590	1.09
CG-121K	1/2"	.276 - .472	7 - 12	.809	.590	1.09
CG-122K	1/2"	.394 - .551	10 - 14	.809	.590	1.21
CG-131K	3/4"	.551 - .709	13 - 18	1.020	.590	1.49
CG-140K	1"	.709 - .984	18 - 25	1.275	.709	1.89



*PG and Metric Style Threads Available. Comes complete with Locknut and Gasket



IBOCO

26 Northfield Avenue, Edison, NJ 08837 Tel: 732-417-0066 Fax: 732 417-1166

email: iboco@iboco.com website: www.iboco.com