



ZODZ2.E123572 Positioning Devices - Component

[Page Bottom](#)

Positioning Devices - Component

[See General Information for Positioning Devices - Component](#)

IBOCO CORP

E123572

26 NORTHFIELD AVE
EDISON, NJ 08837 USA

Plastic wiring ducts, Cat. No. TD followed by 25x25, 25x50, 37,5x25, 37,5x50, 37,5x75, 50x37,5, 50x50, 50x75, 75x50, 75x75, 75x125, 100x50, 100x75, 100x125, 125x50, or 125x75 followed by G. For use at temperatures not exceeding 50°C.

Cat. No. TD- followed by 1010, 1020, 1510, 1520, 1530, 2015, 2020, 2030, 3020, 3030, 3050, 4020, 4030, 4050, 5020, or 5030, followed by G. For use at temperatures not exceeding 50°C.

Cat. No. T1 followed by 15x18, 15x30, 15x40, 15x60, 25x30, 25x40, 25x60, 25x80, 25x100, 40x40, 40x60, 40x80, 40x100, 60x40, 60x60, 60x80, 60x100, 75x125, 80x40, 80x60, 80x80, 80x100, 100x40, 100x60, 100x80, 100x100, 100x125, 120x60, 120x80, or 150x100 followed by G, W, A or BL. For use at temperatures not exceeding 50°C.

Cat. No. T1- followed by 0506, 0510, 0515, 0522, 1010, 1015, 1022, 1030, 1040, 1515, 1522, 1530, 1540, 2215, 2222, 2230, 2240, 3050, 3015, 3022, 3030, 3040, 4015, 4022, 4030, 4040, 4050, 5022, 5030, or 6040 followed by G,W,A,K,BL or B. For use at temperatures not exceeding 50°C.

Cat. No. T1-E followed by 25x40, 25x60, 25x80, 25x100, 40x40, 40x60, 40x80, 40x100, 60x40, 60x60, 60x80, 60x100, 80x40, 80x60, 80x80, 80x100, 100x40, 100x60, 100x80, 100x100, 120x60, 120x80, or 150x100 followed by G,W,A or BL. For use at temperatures not exceeding 50°C.

Cat. No. T1E- followed by 1015, 1022, 1030, 1040, 1515, 1522, 1530, 1540, 2215, 2222, 2230, 2240, 3015, 3022, 3030, 3040, 4015, 4022, 4030, 4040, 5022, 5030, 6040 followed by G, W, A, K, BL or B. For use at temperatures not exceeding 50°C.

Cat. No. T1-EF followed by 25x80, 25x100, 40x80, 40x100, 60x80, 60x100, 80x80, 80x100, 100x80, 100x100, 120x60, 120x80, or 150x100 followed by G,W,A,K,B or BL. For use at temperatures not exceeding 50°C.

Cat. No. T1EF- followed by 1030, 1040, 1530, 1540, 2230, 2240, 3030, 3040, 4030, 4040, 5022, 5030 or 6040 followed by G,W,A,K,B or BL. For use at temperatures not exceeding 50°C.

Cat. No. T1-F followed by 25x80, 25x100, 40x80, 40x100, 60x80, 60x100, 80x80, 80x100, 100x80, 100x100, 120x60, 120x80, or 150x100 followed by G,W,A,K,BL or B. For use at temperatures not exceeding 50°C.

Cat. No. T1F- followed by 1030, 1040, 1530, 1540, 2230, 2240, 3030, 3040, 4030, 4040, 5022, 5030, or 6040 followed by G, W, A, K, BL or B. For use at temperatures not exceeding 50°C.

Cat. No. T1-N followed by 25x30, 25x40, 25x60, 25x80, 25x100, 40x40, 40x60, 40x80, 40x100, 60x40, 60x60, 60x80, 60x100, 80x40, 80x60, 80x80, 80x100, 100x40, 100x60, 100x80, 100x100, 120x60, 120x80, 150x100 followed by G. For use at temperatures not exceeding 50°C.

Cat. No. T1N- followed by 1010, 1015, 1022, 1030, 1040, 1515, 1522, 1530, 1540, 2215, 2222, 2230, 2240, 3015, 3022, 3030, 3040, 4015, 4022, 4030, 4040, 5022, 5030, 6040 followed by G. For use at temperatures not exceeding 50°C.

Cat. No. T1-EN followed by 25x40, 25x60, 25x80, 25x100, 40x40, 40x60, 40x80, 40x100, 60x40, 60x60, 60x80, 60x100, 80x40, 80x60, 80x80, 80x100, 100x40, 100x60, 100x80, 100x100, 120x60, or 120x80 followed by G. For use at temperatures not exceeding 50°C.

Cat. No. T1EN- followed by 1015, 1022, 1030, 1040, 1515, 1522, 1530, 1540, 2215, 2222, 2230, 2240, 3015, 3022, 3030, 3040, 4015, 4022, 4030, 4040, 5022, or 5030 followed by G. For use at temperatures not exceeding 50°C.

Cat. No. TS-H followed by 15x18, 15x30, 25x30, 25x40, 25x80, 40x40, 40x60, 40x80, 60x60, 60x80, 80x60, 80x80, 80x100, 100x80, or 100x100 followed by G. For use at temperatures not exceeding 50°C.

Cat. No. TSH- followed by 0506, 0510, 1010, 1015, 1030, 1515, 1522, 1530, 2222, 2230, 3022, 3030, 3040, 4030, or 4040 followed by G. For use at temperatures not exceeding 50°C.

Cat. No. TS followed by 15x18, 15x30, 25x30, 25x40, 25x80, 40x40, 40x60, 40x80, 60x60, 60x80, 80x60, 80x80, 80x100, 100x80, or 100x100 followed by G. For use at temperatures not exceeding 50°C.

Cat. No. TS- followed by 0506, 0510, 1010, 1015, 1030, 1515, 1522, 1530, 2222, 2230, 3022, 3030, 3040, 4030, or 4040 followed by G. For use at temperatures not exceeding 50°C.

Cat. Nos. Open, T1H-1015LG, T1H-1020LG, T1H-1030LG, T1H-1515LG, T1H-1520LG, T1H-1530LG, T1H-2020LG, T1H-2030LG, T1H-2040LG, T1H-3020LG, T1H-3030LG, T1H-3040LG, T1H-4020LG, T1H-4030LG, T1H-4040LG, T1-H 25x37.5 LG, T1-H 25x50 LG, T1-H 25x75 LG, T1-H 37.5x37.5 LG, T1-H 37.5x50 LG, T1-H 37.5x75 LG, T1-H 50x50 LG, T1-H 50x75 LG, T1-H 50x100 LG, T1-H 75x50 LG, T1-H 75x75 LG, T1-H 75x100 LG, T1-H 100x50 LG, T1-H 100x75 LG, T1-H 100x100 LG for use at temperatures not exceeding 65 C.

Cat. Nos. Narrow, T1EH-1515LG, T1EH-1520LG, T1EH-1530LG, T1EH-2020LG, T1EH-2030LG, T1EH-2040LG, T1EH-3020LG, T1EH-3030LG, T1EH-3040LG, T1EH-4020LG, T1EH-4030LG, T1EH-4040LG, T1-EH 37.5x37.5 LG, T1-EH 37.5x50 LG, T1-EH 37.5x75 LG, T1-EH 50x50 LG, T1-EH 50x75 LG, T1-EH 50x100 LG, T1-EH 75x50 LG, T1-EH 75x75 LG, T1-EH 75x100 LG, T1-EH 100x50 LG, T1-EH 100x75 LG, T1-EH 100x100 LG for use at temperatures not exceeding 65 C.

Slotted flexible cable ducts, designated "Dinosaur", Cat. Nos. DN-10A W, DN-20A W, DN-30A W, DN-40A W, DN-25AW, DN-35AW, DN-45AW, for use at temperatures not exceeding 80°C.

Cat. Nos. DN-25AG, DN-AS, DN-35AG, DN-AM, DN-45AG, DN-AL, for use at temperatures not exceeding 65°C.

Marking: Company name, the product designation and factory identification, if applicable, on the product of smallest unit package.

Last Updated on 2010-10-22

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

